
epd-norge
Global program operatør

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

TSLF 24kV 1x 400/35A



The Norwegian EPD Foundation

Owner of the declaration:
Elektroskandia Norge AS

Product:
TSLF 24kV 1x 400/35A

Declared unit:
1 m

This declaration is based on Product Category Rules:
CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 027:2020 Part B for Electrical cables and wires

Program operator:
The Norwegian EPD Foundation

Declaration number:
289499

Registration number:
289499

Issue date:
09.04.2024

Valid to:
09.04.2029

EPD software:
LCAno EPD generator ID: 308953

General information

Product

TSLF 24kV 1x 400/35A

Owner of the declaration:

Elektroskandia Norge AS
Contact person: Nils - Arne Grande
Phone: +47 97 66 22 12
e-mail: nils-arne.grande@onninen.com

Program operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-norge.no

Manufacturer:

Top Cable S. A.

Declaration number:

289499

Place of production:

Top Cable S. A.
Leonardo Da Vinci Num. 1
08191 Rubí (Barcelona), Spain

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 027:2020 Part B for Electrical cables and wires

Management system:

ISO 14001, ISO 9001

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Organisation no:

977 454 700

Declared unit:

1 m TSLF 24kV 1x 400/35A

Issue date:

09.04.2024

Declared unit with option:

A1,A2,A3,A4,A5,B1,B2,B3,B4,B5,B6,B7,C1,C2,C3,C4,D

Valid to:

09.04.2029

Year of study:

2023

Functional unit:

1 m of TSLF 24kV 1X400 /35A electrical cable installed and used to transmit a reference electric current of 1A over 40 years, including waste treatment at end-of-life.

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway. Approval number:

Developer of EPD: Miguel Angel Gago - Top Cable S. A.

Reviewer of company-specific input data and EPD: Nils Arne Grande, Elektroskandia Norge AS

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools. Approval number: NEPDT32.

Approved:

Third party verifier:

Vito D'Incognito, Take Care International

(no signature required)

Product

Product description:

TSLF 24kV 1x400/35A

Product specification

TOPCABLE_TSLF eng

Materials	kg	%
Metal - Aluminium	1,15	50,69
Metal - Copper	0,15	6,79
Plastic - Polyethylene	0,67	29,37
Plastic - Polyethylene (MDPE)	0,28	12,22
Tape	0,02	0,93
Total	2,27	

Packaging	kg	%
Packaging - Plastic	0,00	100,00
Total incl. packaging	2,27	

Technical data:

Produced based on the standard:
CENELEC HD 620 Part 10 Section K

Market:

Norway

Reference service life, product

40 years. Standard lifetime for energy distribution network applications, provided in appendix 1 of PSR for wires, cables, and accessories of PEP Ecopassport.

Reference service life, building or construction works

40 years. Estimation made to match the product service life and keep the EPD environmental impact calculations at the product level.

LCA: Calculation rules

Declared unit:

1 m TSLF 24kV 1x 400/35A

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.


Materials	Source	Data quality	Year
Metal - Aluminium	ecoinvent 3.6	Database	2019
Metal - Copper	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Plastic - Polyethylene	ecoinvent 3.6	Database	2019
Plastic - Polyethylene (MDPE)	ecoinvent 3.6	Database	2019
Tape	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

System boundary:

The flowchart below illustrates the system boundaries of the analysis:



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Module A4 = Transport distance of 2.600 km from Top Cable production site to Elektroskandia's warehouse in Langhus was included. A distance of 300 Km was then added as additional transport to market.

Modules A5 = 2 % product losses during installation are estimated by the company. No energy use for installation has been quantified since this operation is assumed to be done with other products and should be assessed at a construction works level. Cable drums are reused and assumed under the cut-off criterion of 1%.

Modules B1, B2, B3, B5, and B7 = Company data shows that no significant activities have been reported for use, maintenance, repair, replacement, refurbishment, and water use. This reflects an absence of impacts during the 40 years reference service life of the cable in these modules.

Module B4 = The service life of the building is the same as the service life of the product, no replacement activities are taking place in module B4.

Module B6 = The operational energy use of the cable is calculated based on the methodology described in PEP Ecopassport, Product Specific Rules (PSR) for wires, cables and accessories, reference PSR-0001-ed3-EN-2015 10 16. The following parameters are used to calculate the electricity loss of the cable:
- Reference service life = 40 years (according to appendix 1 of the PSR)
- Number of conductors = 1 unit
- Use rate = 100% percent (according to appendix 1 of the PSR)
- Linear conductor resistivity = 0,000125 Ohm per meter
- Current intensity = 1 Ampere

Module C1 = For both buildings and construction works, cables will be taken out as part of a larger demolition. The energy use for cable removal compared to other heaver materials is assumed to be low. This module can therefore be included with zero impact.

Module C2 = A distance of 300 km was also added as additional transport to market.

Modules C3 and C4 = Waste treatment of the product follows the default values provided in EN 50693, Product Category Rules for life cycle assessments of electronic and electrical products and systems, table G.4. This table specified how different types of raw materials used in A1 will likely be treated during the end-of-life of the product. Waste treatments in C3 include material recycling and incineration with and without energy recovery and fly ash extraction. Disposal in C4 consist of landfilling of different waste fractions and of ashes.

Module D = The recyclability of metals and plastics allows the producers a credit for the net scrap that is produced at the end of a product's life. The benefits from recycling of net scrap are described in formula from EN 15804:2012+A2:2019. Substitution of heat and electricity generated by the incineration with energy recovery of plastic insulation and other parts is also calculated in module D.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36,7 %	2900	0,043	l/tkm	124,70

Assembly (A5)	Unit	Value			
Product loss during installation (percentage of cable)	Units/DU	0,00			
Waste, plastic, mixture, to average treatment - A5 including transport (kg)	kg	0,00			

Operational energy (B6)	Unit	Value			
Electricity, Norway (kWh)	kWh/DU	0,04			

Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36,7 %	300	0,043	l/tkm	12,90

Waste processing (C3)	Unit	Value			
Aluminium to recycling (kg)	kg	0,80			
Copper to recycling (kg)	kg	0,09			
Waste treatment of plastic mixture, incineration with energy recovery and fly ash extraction (kg)	kg	0,01			
Waste treatment of polyethylene (PE), incineration with energy recovery and fly ash extraction (kg)	kg	0,47			

Disposal (C4)	Unit	Value			
Landfilling of aluminium (kg)	kg	0,34			
Landfilling of ashes from incineration of Plastic mixture, process per kg ashes and residues (kg)	kg	0,00			
Landfilling of ashes from incineration of Polyethylene (PE), process per kg ashes and residues (kg)	kg	0,02			
Landfilling of copper (kg)	kg	0,06			
Landfilling of plastic mixture (kg)	kg	0,48			

Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of electricity (MJ)	MJ	0,93			
Substitution of primary aluminium with net scrap (kg)	kg	0,62			
Substitution of primary copper with net scrap (kg)	kg	0,13			
Substitution of thermal energy, district heating (MJ)	MJ	14,08			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact

Indicator	Unit	A1	A2	A3	A4	A5	B1	B2	B3
GWP-total	kg CO_2 -eq	1,85E+01	1,27E-01	1,39E-01	1,07E+00	2,15E-02	0	0	0
GWP-fossil	kg CO_2 -eq	1,81E+01	1,27E-01	1,27E-01	1,07E+00	2,11E-02	0	0	0
GWP-biogenic	kg CO_2 -eq	1,58E-01	5,25E-05	1,24E-02	4,45E-04	1,71E-04	0	0	0
GWP-luluc	kg CO_2 -eq	1,95E-01	4,51E-05	3,75E-04	3,82E-04	1,96E-04	0	0	0
ODP	kg CFC11 -eq	1,27E-06	2,87E-08	1,27E-08	2,43E-07	1,59E-09	0	0	0
AP	mol H+ -eq	1,47E-01	3,64E-04	1,14E-03	3,09E-03	1,52E-04	0	0	0
EP-FreshWater	kg P -eq	9,79E-04	1,01E-06	5,89E-06	8,58E-06	9,96E-07	0	0	0
EP-Marine	kg N -eq	1,77E-02	7,21E-05	3,11E-04	6,11E-04	1,90E-05	0	0	0
EP-Terrestial	mol N -eq	2,04E-01	8,07E-04	4,44E-03	6,83E-03	2,18E-04	0	0	0
POCP	kg NMVOC -eq	6,55E-02	3,09E-04	8,89E-04	2,62E-03	7,00E-05	0	0	0
ADP-minerals&metals[1]	kg Sb-eq	6,54E-04	3,50E-06	8,59E-06	2,97E-05	6,99E-07	0	0	0
ADP-fossil[1]	MJ	2,66E+02	1,92E+00	9,59E-01	1,62E+01	2,87E-01	0	0	0
WDP[1]	m^3	6,10E+03	1,85E+00	3,29E+00	1,57E+01	6,12E+00	0	0	0

Indicator	Unit	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-total	kg CO_2 -eq	0	0	1,07E-03	0	0	1,11E-01	1,45E+00	6,18E-02	-6,00E+00
GWP-fossil	kg CO_2 -eq	0	0	1,03E-03	0	0	1,11E-01	1,45E+00	6,18E-02	-5,87E+00
GWP-biogenic	kg CO_2 -eq	0	0	2,86E-05	0	0	4,60E-05	1,20E-05	5,39E-06	-2,68E-02
GWP-luluc	kg CO_2 -eq	0	0	4,26E-06	0	0	3,95E-05	1,79E-06	3,48E-06	-1,07E-01
ODP	kg CFC11 -eq	0	0	7,10E-11	0	0	2,52E-08	1,14E-09	3,23E-09	-5,95E-03
AP	mol H+ -eq	0	0	8,07E-06	0	0	3,19E-04	1,84E-04	8,58E-05	-9,11E-02
EP-FreshWater	kg P -eq	0	0	7,43E-08	0	0	8,88E-07	1,14E-07	1,68E-07	-5,79E-04
EP-Marine	kg N -eq	0	0	8,87E-07	0	0	6,32E-05	8,81E-05	8,78E-05	-7,09E-03
EP-Terrestial	mol N -eq	0	0	1,15E-05	0	0	7,07E-04	9,51E-04	3,43E-04	-8,78E-02
POCP	kg NMVOC -eq	0	0	3,11E-06	0	0	2,71E-04	2,28E-04	1,09E-04	-2,72E-02
ADP-minerals&metals[1]	kg Sb-eq	0	0	7,70E-08	0	0	3,07E-06	5,25E-08	8,59E-08	-2,91E-04
ADP-fossil[1]	MJ	0	0	1,41E-02	0	0	1,68E+00	9,64E-02	2,53E-01	-7,36E+01
WDP[1]	m^3	0	0	2,46E+00	0	0	1,62E+00	2,35E-01	4,51E+00	-3,13E+03

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator		Unit	A1	A2	A3	A4	A5	B1	B2	B3
	PM	Disease incidence	1,19E-06	7,76E-09	1,40E-08	6,58E-08	1,29E-09	0	0	0
	IRP[2]	kgBq U235 -eq	8,44E-01	8,38E-03	3,26E-03	7,10E-02	9,36E-04	0	0	0
	ETP-fw[1]	CTUe	7,81E+02	1,42E+00	9,34E+00	1,20E+01	1,06E+00	0	0	0
	HTP-c[1]	CTUh	3,96E-08	0,00E+00	1,73E-10	0,00E+00	4,00E-11	0	0	0
	HTP-nc[1]	CTUh	1,06E-06	1,55E-09	5,02E-09	1,32E-08	1,09E-09	0	0	0
	SQP[1]	dimensionless	4,07E+01	1,34E+00	3,67E+01	1,14E+01	9,23E-02	0	0	0

Indicator		Unit	B4	B5	B6	B7	C1	C2	C3	C4	D
	PM	Disease incidence	0	0	5,80E-11	0	0	6,80E-09	7,22E-10	1,58E-09	-5,30E-07
	IRP[2]	kgBq U235 -eq	0	0	2,56E-04	0	0	7,34E-03	1,66E-04	1,48E-03	-3,14E-01
	ETP-fw[1]	CTUe	0	0	6,42E-02	0	0	1,25E+00	3,30E-01	2,52E+02	-5,80E+02
	HTP-c[1]	CTUh	0	0	3,00E-12	0	0	0,00E+00	3,20E-11	1,60E-11	-2,09E-08
	HTP-nc[1]	CTUh	0	0	7,20E-11	0	0	1,36E-09	1,26E-09	3,14E-10	-7,62E-07
	SQP[1]	dimensionless	0	0	7,10E-03	0	0	1,18E+00	1,19E-02	6,75E-01	-1,46E+01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use

Indicator		Unit	A1	A2	A3	A4	A5	B1	B2	B3
	PERE	MJ	5,55E+01	2,74E-02	9,20E+00	2,32E-01	6,50E-02	0	0	0
	PERM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0	0	0
	PERT	MJ	5,55E+01	2,74E-02	9,20E+00	2,32E-01	6,50E-02	0	0	0
	PENRE	MJ	2,27E+02	1,92E+00	9,60E-01	1,62E+01	2,49E-01	0	0	0
	PENRM	MJ	4,09E+01	0,00E+00	0,00E+00	0,00E+00	-2,08E-02	0	0	0
	PENRT	MJ	2,68E+02	1,92E+00	9,60E-01	1,62E+01	2,28E-01	0	0	0
	SM	kg	2,13E-01	0,00E+00	0,00E+00	0,00E+00	2,13E-04	0	0	0
	RSF	MJ	4,00E-01	9,82E-04	2,19E-03	8,32E-03	4,14E-04	0	0	0
	NRSF	MJ	5,88E-02	3,51E-03	4,33E-03	2,97E-02	1,02E-04	0	0	0
	FW	m^3	3,36E-01	2,05E-04	2,51E-03	1,74E-03	3,41E-04	0	0	0

Indicator		Unit	B4	B5	B6	B7	C1	C2	C3	C4	D
	PERE	MJ	0	0	1,83E-01	0	0	2,40E-02	2,92E-03	2,44E-02	-3,35E+01
	PERM	MJ	0	0	0,00E+00	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	PERT	MJ	0	0	1,83E-01	0	0	2,40E-02	2,92E-03	2,44E-02	-3,35E+01
	PENRE	MJ	0	0	1,41E-02	0	0	1,68E+00	9,65E-02	2,53E-01	-7,36E+01
	PENRM	MJ	0	0	0,00E+00	0	0	0,00E+00	-4,05E+01	0,00E+00	0,00E+00
	PENRT	MJ	0	0	1,41E-02	0	0	1,68E+00	-4,04E+01	2,54E-01	-7,36E+01
	SM	kg	0	0	0,00E+00	0	0	0,00E+00	0,00E+00	2,75E-07	9,30E-02
	RSF	MJ	0	0	1,43E-04	0	0	8,60E-04	8,12E-05	5,08E-04	-2,70E-03
	NRSF	MJ	0	0	3,57E-04	0	0	3,08E-03	0,00E+00	1,86E-03	-3,71E-01
	FW	m^3	0	0	1,36E-03	0	0	1,80E-04	2,92E-04	3,22E-04	-1,54E-01

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

End of life - Waste

Indicator		Unit	A1	A2	A3	A4	A5	B1	B2	B3
	HWD	kg	1,35E-01	9,89E-05	2,38E-02	8,38E-04	1,89E-04	0	0	0
	NHWD	kg	4,18E+00	9,32E-02	4,08E-02	7,90E-01	6,59E-03	0	0	0
	RWD	kg	7,97E-04	1,31E-05	3,78E-06	1,11E-04	9,37E-07	0	0	0

Indicator		Unit	B4	B5	B6	B7	C1	C2	C3	C4	D
	HWD	kg	0	0	9,05E-06	0	0	8,66E-05	0,00E+00	2,93E-02	1,94E-02
	NHWD	kg	0	0	1,09E-03	0	0	8,17E-02	0,00E+00	9,02E-01	-1,77E+00
	RWD	kg	0	0	1,26E-07	0	0	1,14E-05	0,00E+00	1,72E-06	-2,94E-04

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

End of life - Output flow

Indicator		Unit	A1	A2	A3	A4	A5	B1	B2	B3
	CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0	0	0
	MFR	kg	0,00E+00	0,00E+00	4,51E-04	0,00E+00	1,15E-03	0	0	0
	MER	kg	0,00E+00	0,00E+00	9,57E-02	0,00E+00	5,78E-04	0	0	0
	EEE	MJ	0,00E+00	0,00E+00	5,66E-02	0,00E+00	9,87E-04	0	0	0
	EET	MJ	0,00E+00	0,00E+00	8,56E-01	0,00E+00	1,49E-02	0	0	0

Indicator		Unit	B4	B5	B6	B7	C1	C2	C3	C4	D
	CRU	kg	0	0	0,00E+00	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	MFR	kg	0	0	0,00E+00	0	0	0,00E+00	8,97E-01	4,32E-05	-3,64E-03
	MER	kg	0	0	0,00E+00	0	0	0,00E+00	4,82E-01	1,06E-06	-4,79E-04
	EEE	MJ	0	0	0,00E+00	0	0	0,00E+00	9,30E-01	6,86E-05	-1,17E-03
	EET	MJ	0	0	0,00E+00	0	0	0,00E+00	1,41E+01	1,04E-03	-1,78E-02

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

Biogenic Carbon Content

Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0,00E+00
Biogenic carbon content in accompanying packaging	kg C	0,00E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Electricity, renewable with guarantee of origin for 2022, high-medium voltage, Spain (kWh) - Top Cable	ecoinvent 3.6	65,65	g CO2-eq/kWh

Dangerous substances

The product contains no substances on the REACH Candidate list at or above 100 ppm, 0,01 % by weight.

Indoor environment

Not relevant. The cable is intended for outdoor use

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products										
Indicator	**Unit**	A1	A2	A3	A4	A5	B1	B2	B3	
GWPIOBC	kg CO_2 -eq	1,84E+01	1,27E-01	1,38E-01	1,07E+00	2,14E-02	0	0	0	

Indicator	**Unit**	B4	B5	B6	B7	C1	C2	C3	C4	D
GWPIOBC	kg CO_2 -eq	0	0	1,06E-03	0	0	1,11E-01	1,45E+00	6,28E-02	-5,58E+00

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010. Environmental labels and declarations - Type III environmental declarations - Principles and procedures. International Organization for Standardization.
ISO 14044:2006. Environmental management - Life cycle assessment - Requirements and guidelines. International Organization for Standardization.
EN 15804:2012+A2:2019. Environmental product declaration - Core rules for the product category of construction products. European Committee for Standardization.
ISO 21930:2017. Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products. International Organization for Standardization.
EN 50693:2019. Product category rules for life cycle assessments of electronic and electrical products and systems. European Committee for Standardization.
Ecoinvent v3, 2019. Allocation, cut-off by classification. Swiss Centre of Life Cycle Inventories.
Iversen et al., (2021). eEPD v2021.09, background information for EPD generator tool system verification, LCA.no. Report number: 07.21. System verification report.
Philis et al., (2022). EPD generator for NPCR 027 part B for electrical wires and cables, background information for EPD generator application and LCA data, LCA.no Report number: 03.22. PCR verification report.
EPD Norway (2022). NPCR Part A: Construction products and services. The Norwegian EPD foundation. Version 2.0 published 24.03.2021.
EPD Norway (2022). NPCR 027 Part B for electrical cables and wires. The Norwegian EPD foundation. Version 2.0 published 01.03.2022.

	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-norge.no
onninen Elektroskandia Norge	**Owner of the declaration:** Elektroskandia Norge AS Postboks 143, 1403 Langhus	Phone: +47 97 66 22 12 e-mail: nils-arne.grande@onninen.com web: elektroskandia.no
LCA.no	**Author of the Life Cycle Assessment** LCA.no AS Dokka 6B, 1671	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
LCA.no	**Developer of EPD generator** LCA.no AS Dokka 6B,1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
ECO PLATFORM EPD VERIFIED	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal