epd-norge
Global program operatør

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

Profim Sorriso 10V



profim

Flokk

The Norwegian EPD Foundation

Owner of the declaration:
Flokk AS

Product:
Profim Sorriso 10V

Declared unit:
1 pcs

This declaration is based on Product Category Rules:
CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 026:2022 Part B for Furniture

Program operator:
The Norwegian EPD Foundation

Declaration number:

Registration number:

Issue date:

Valid to:

EPD software:
LCAno EPD generator ID: 454324

General information

Product

Profim Sorriso 10V

Program operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-norge.no

Declaration number:

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 026:2022 Part B for Furniture

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 pcs Profim Sorriso 10V

Declared unit (cradle to gate) with option:

A1-A3,A4,A5,B2,B3,B4,C1,C2,C3,C4,D

Functional unit:

Profim Sorriso 10V (Xtreme/Camira) inluding packaging

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

Flokk AS
Contact person: Atle Thiis-Messel
Phone: 0047 98 25 68 30
e-mail: atle.messel@flokk.com

Manufacturer:

Flokk AS
Drammensveien 145,
0277 Oslo, Norway

Place of production:

Flokk - Turek
ul. Górnicza 8
62-700 Turek, Poland

Management system:

ISO 14001, ISO 9001, ISO 50001(Norway, Sweden)

Organisation no:

No 928 902 749

Issue date:

Valid to:

Year of study:

2023

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Monika Kuczynska

Reviewer of company-specific input data and EPD: Damian Bakowski

Approved:

Product

Product description:

Designed by Jaroslaw Szymanski of Studio 1:1, the name of the armchair means 'smile' in Italian. It is distinguished by an elegant, oval shell shape and expressive and precise stitching. It is an ideal solution for modern reception areas, hotels or cafés, where comfort of use is important.

Product specification

The model studied in this declaration is the Profim Sorriso 10V upholstered in the Xtreme fabric from Camira, including packaging. Key environmental indicators for other models within the family, as well as applicable product collection options, are presented in a table on page 12 of this declaration.

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Plastic - Polyoxymethylene (POM)	0,01	0,04	0,00	0,00
Metal - Brass	0,01	0,10	0,00	17,71
Printed paper	0,00	0,01	0,00	34,31
Plastic - Polyurethane (PUR)	4,14	30,50	0,00	0,00
Textile - Polyester (PE)	1,23	9,05	0,98	79,86
Powder coating	0,02	0,15	0,00	0,00
Metal - Steel	7,61	56,13	1,49	19,59
Plastic - Polyethylene (LDPE)	0,43	3,17	0,00	0,00
Adhesive	0,01	0,07	0,00	2,54
Plastic - Polypropylene (PP)	0,09	0,65	0,00	0,00
Plastic - Polyamide	0,02	0,13	0,00	0,00
Total	13,56	100,00	2,47	

Packaging	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Packaging - Plastic	0,07	1,54	0,00	0,00
Packaging - Plastic straps	0,03	0,68	0,00	0,00
Recycled cardboard	4,42	97,20	4,42	100,00
Packaging - Paper	0,03	0,57	0,01	34,31
Total incl. packaging	18,11	100,00	6,90	

Technical data:

- frame: metal wire with cross section fi 16 mm
- Colour variants: MetallicPro, Chrome and Black (RAL 9005)
- glides: teflon glides or felt glides
- seat (cushion): cold molded foam - density 85 kg/m3
- shell: metal frame; cold molded foam - density 80 kg/m3
- possibility of mixing colours of the same fabric on shell and seat cushion

Market:

Worldwide

Reference service life, product

5 years

Reference service life, building

LCA: Calculation rules

Declared unit:

1 pcs Profim Sorriso 10V

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Adhesive	Modified ecoinvent 3.6	Database/Supplier	2019
Metal - Brass	ecoinvent 3.6	Database	2019
Metal - Steel	ecoinvent 3.6	Database	2019
Metal - Steel	Modified ecoinvent 3.6	Database	2019
Packaging - Paper	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Plastic straps	ecoinvent 3.6	Database	2019
Plastic - Polyamide	Modified ecoinvent 3.6	Database	2019
Plastic - Polyethylene (LDPE)	ecoinvent 3.6	Database	2019
Plastic - Polyoxymethylene (POM)	ecoinvent 3.6	Database	2019
Plastic - Polypropylene (PP)	ecoinvent 3.6	Database	2019
Plastic - Polyurethane (PUR)	ecoinvent 3.6	Database	2019
Powder coating	Ecoinvent 3.6	Database	2019
Printed paper	ecoinvent 3.6	Database	2019
Recycled cardboard	Modified ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	Modified ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	X	X	MND	MND	MND	X	X	X	X	X

System boundary:



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 5 (km)	53,3 %	1000	0,023	l/tkm	23,00

Assembly (A5)	Unit	Value			
Waste, packaging, cardboard, 100 % recycled, to average treatment (kg)	kg	4,42			
Waste, packaging, paper printed, to average treatment (kg)	kg	0,03			
Waste, packaging, PET straps, to average treatment - A5 (kg)	kg	0,03			
Waste, packaging, plastic film (LDPE), to average treatment - A5 (kg)	kg	0,07			

Maintenance (B2)	Unit	Value			
Electricity, European average (kWh)	kWh/DU	10,53			
Electricity, World average (kWh)	kWh/DU	1,17			
Water, tap water (m3)	m3/DU	0,78			

Repair (B3)	Unit	Value			
Electricity, European average (kWh)	kWh/DU	0,50			
Electricity, World average (kWh)	kWh/DU	0,06			

Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	36,7 %	85	0,044	l/tkm	3,74

Waste processing (C3)	Unit	Value			
Waste treatment per kg Graphical paper, incineration with fly ash extraction (kg)	kg	0,00			
Waste treatment per kg Hazardous waste, incineration (kg)	kg	0,01			
Waste treatment per kg Non-hazardous waste, incineration with fly ash extraction - C3 (kg)	kg	0,02			
Waste treatment per kg Polyethylene, PE, incineration with fly ash extraction - C3 (kg)	kg	0,43			
Waste treatment per kg Polyoxymethylene (POM), incineration with fly ash extraction (kg) - CH - C3	kg	0,01			
Waste treatment per kg Polypropylene (PP), incineration with fly ash extraction - C3 (kg)	kg	0,09			
Waste treatment per kg Polyurethane (PU), incineration (kg)	kg	4,14			
Waste treatment per kg Scrap copper, incineration with fly ash extraction (kg)	kg	0,01			
Waste treatment per kg Scrap steel, incineration with fly ash extraction (kg)	kg	7,61			
Waste treatment per kg Textile, incineration with fly ash extraction (kg)	kg	1,25			
Waste, materials to recycling (kg)	kg	2,58			

Disposal (C4)	Unit	Value			
Landfilling of ashes and residues from incineration of Scrap copper (kg)	kg	0,01			
Landfilling of ashes and residues from incineration of Scrap steel (kg)	kg	5,03			
Landfilling of ashes from incineration of Graphical paper, process of ashes and residues (kg)	kg	0,00			
Landfilling of ashes from incineration of Hazardous waste, from incineration (kg)	kg	0,00			
Landfilling of ashes from incineration of Non-hazardous waste, process per kg ashes and residues - C4 (kg)	kg	0,00			
Landfilling of ashes from incineration of Polyethylene, PE, process per kg ashes and residues - C4 (kg)	kg	0,02			
Landfilling of ashes from incineration of Polyoxymethylene (POM), process per kg ashes and residues (kg) - CH - C4	kg	0,00			
Landfilling of ashes from incineration of Polypropylene, PP, process per kg ashes and residues - C4 (kg)	kg	0,00			
Landfilling of ashes from incineration of Polyurethane (PU), process per kg ashes and residues - C4 (kg)	kg	0,16			
Landfilling of ashes from incineration of Textile, soiled, process per kg ashes and residues (kg)	kg	0,06			

Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of electricity, in Norway (MJ)	MJ	7,94			
Substitution of primary Brass with net scrap (kg)	kg	0,00			
Substitution of primary steel with net scrap (kg)	kg	2,08			
Substitution of thermal energy, district heating, in Norway (MJ)	MJ	120,10			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact							
Indicator		Unit	A1-A3	A4	A5	B2	B3
	GWP-total	kg CO_2 -eq	5,01E+01	1,65E+00	7,63E+00	5,67E+00	2,54E-01
	GWP-fossil	kg CO_2 -eq	5,68E+01	1,65E+00	7,99E-02	5,62E+00	2,52E-01
	GWP-biogenic	kg CO_2 -eq	-6,75E+00	6,75E-04	7,55E+00	3,61E-02	1,62E-03
	GWP-luluc	kg CO_2 -eq	6,38E-02	4,80E-04	2,44E-05	1,27E-02	5,74E-04
	ODP	kg CFC11 -eq	2,93E-06	3,80E-07	1,57E-08	4,39E-07	1,95E-08
	AP	mol H+ -eq	2,91E-01	6,92E-03	3,50E-04	3,22E-02	1,44E-03
	EP-FreshWater	kg P -eq	3,31E-03	1,25E-05	6,07E-07	5,47E-04	2,47E-05
	EP-Marine	kg N -eq	6,43E-02	2,08E-03	1,22E-04	4,31E-03	1,91E-04
	EP-Terrestial	mol N -eq	6,08E-01	2,30E-02	1,25E-03	5,22E-02	2,32E-03
	POCP	kg NMVOC -eq	2,12E-01	7,40E-03	3,62E-04	1,35E-02	5,94E-04
	ADP-minerals&metals[1]	kg Sb-eq	1,60E-03	2,81E-05	1,79E-06	4,34E-05	1,69E-06
	ADP-fossil[1]	MJ	8,77E+02	2,56E+01	1,04E+00	1,08E+02	4,87E+00
	WDP[1]	m^3	1,42E+04	1,96E+01	1,39E+00	1,51E+03	6,70E+01

Indicator		Unit	B4	C1	C2	C3	C4	D
	GWP-total	kg CO_2 -eq	0	0	2,57E-01	1,46E+01	6,94E-02	-3,01E+00
	GWP-fossil	kg CO_2 -eq	0	0	2,57E-01	1,28E+01	6,93E-02	-2,99E+00
	GWP-biogenic	kg CO_2 -eq	0	0	1,05E-04	1,82E+00	5,64E-05	-2,73E-03
	GWP-luluc	kg CO_2 -eq	0	0	8,97E-05	8,14E-05	1,88E-05	-2,50E-02
	ODP	kg CFC11 -eq	0	0	5,85E-08	6,25E-08	1,86E-08	-5,07E-02
	AP	mol H+ -eq	0	0	1,05E-03	1,02E-02	4,39E-04	-1,76E-02
	EP-FreshWater	kg P -eq	0	0	2,01E-06	5,12E-06	7,38E-07	-2,06E-04
	EP-Marine	kg N -eq	0	0	3,11E-04	5,64E-03	1,54E-04	-4,25E-03
	EP-Terrestial	mol N -eq	0	0	3,44E-03	5,41E-02	1,71E-03	-4,46E-02
	POCP	kg NMVOC -eq	0	0	1,05E-03	1,29E-02	4,91E-04	-1,71E-02
	ADP-minerals&metals[1]	kg Sb-eq	0	0	6,95E-06	2,34E-06	1,03E-06	-7,59E-05
	ADP-fossil[1]	MJ	0	0	3,87E+00	5,05E+00	1,39E+00	-2,92E+01
	WDP[1]	m^3	0	0	3,69E+00	1,49E+01	3,84E+00	-5,58E+00

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator		Unit	A1-A3	A4	A5	B2	B3
	PM	Disease incidence	4,30E-06	1,45E-07	5,20E-09	1,14E-07	4,75E-09
	IRP[2]	kgBq U235 -eq	1,69E+00	1,12E-01	4,45E-03	8,90E-01	4,03E-02
	ETP-fw[1]	CTUe	2,73E+03	1,87E+01	1,37E+00	8,66E+01	3,84E+00
	HTP-c[1]	CTUh	1,53E-07	0,00E+00	4,10E-11	2,79E-09	9,70E-11
	HTP-nc[1]	CTUh	1,56E-06	1,81E-08	1,72E-09	8,81E-08	3,37E-09
	SQP[1]	dimensionless	2,15E+02	2,94E+01	7,33E-01	2,53E+01	1,13E+00

Indicator		Unit	B4	C1	C2	C3	C4	D
	PM	Disease incidence	0	0	1,85E-08	4,55E-08	7,75E-09	-5,38E-07
	IRP[2]	kgBq U235 -eq	0	0	1,69E-02	8,37E-03	5,66E-03	-5,56E-02
	ETP-fw[1]	CTUe	0	0	2,85E+00	3,23E+01	9,79E-01	-1,86E+02
	HTP-c[1]	CTUh	0	0	0,00E+00	1,14E-09	3,80E-11	-1,20E-08
	HTP-nc[1]	CTUh	0	0	3,08E-09	3,53E-08	1,14E-09	1,82E-07
	SQP[1]	dimensionless	0	0	2,67E+00	6,18E-01	3,11E+00	-6,81E+01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use

Indicator		Unit	A1-A3	A4	A5	B2	B3
	PERE	MJ	1,50E+02	3,22E-01	1,74E-02	1,99E+01	9,05E-01
	PERM	MJ	2,62E+01	0,00E+00	-2,62E+01	0,00E+00	0,00E+00
	PERT	MJ	1,76E+02	3,22E-01	-2,62E+01	1,99E+01	9,05E-01
	PENRE	MJ	6,96E+02	2,56E+01	1,04E+00	1,08E+02	4,88E+00
	PENRM	MJ	1,82E+02	0,00E+00	-3,69E+00	0,00E+00	0,00E+00
	PENRT	MJ	8,78E+02	2,56E+01	-2,65E+00	1,08E+02	4,88E+00
	SM	kg	6,90E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	RSF	MJ	6,45E-01	1,13E-02	5,71E-04	1,38E+00	6,27E-02
	NRSF	MJ	2,19E-01	3,78E-02	2,32E-03	3,70E-01	1,51E-02
	FW	m^3	8,69E-01	2,92E-03	4,92E-04	8,69E-01	3,99E-03

Indicator		Unit	B4	C1	C2	C3	C4	D
	PERE	MJ	0	0	5,46E-02	1,59E-01	3,10E-02	-6,31E+01
	PERM	MJ	0	0	0,00E+00	-1,41E-02	0,00E+00	0,00E+00
	PERT	MJ	0	0	5,46E-02	1,45E-01	3,10E-02	-6,31E+01
	PENRE	MJ	0	0	3,87E+00	5,08E+00	1,39E+00	-2,92E+01
	PENRM	MJ	0	0	0,00E+00	-1,78E+02	0,00E+00	0,00E+00
	PENRT	MJ	0	0	3,87E+00	-1,73E+02	1,39E+00	-2,92E+01
	SM	kg	0	0	0,00E+00	0,00E+00	0,00E+00	-3,74E-04
	RSF	MJ	0	0	1,95E-03	3,73E-03	8,05E-04	7,16E-02
	NRSF	MJ	0	0	6,98E-03	0,00E+00	4,70E-02	-1,24E+00
	FW	m^3	0	0	4,07E-04	1,73E-02	1,26E-03	-7,90E-02

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

End of life - Waste

Indicator		Unit	A1-A3	A4	A5	B2	B3
	HWD	kg	3,44E-01	1,40E-03	0,00E+00	1,87E-02	8,39E-04
	NHWD	kg	1,16E+01	2,23E+00	4,55E+00	4,24E-01	1,73E-02
	RWD	kg	1,64E-03	1,75E-04	0,00E+00	7,21E-04	3,26E-05

Indicator		Unit	B4	C1	C2	C3	C4	D
	HWD	kg	0	0	1,97E-04	0,00E+00	5,15E+00	-1,24E-02
	NHWD	kg	0	0	1,85E-01	3,00E-02	1,60E-01	-1,17E+00
	RWD	kg	0	0	2,64E-05	0,00E+00	8,50E-06	-4,60E-05

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

End of life - Output flow

Indicator		Unit	A1-A3	A4	A5	B2	B3
	CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	MFR	kg	8,33E-01	0,00E+00	4,19E+00	0,00E+00	0,00E+00
	MER	kg	6,61E-06	0,00E+00	1,83E-03	0,00E+00	0,00E+00
	EEE	MJ	4,60E-01	0,00E+00	2,54E-01	0,00E+00	0,00E+00
	EET	MJ	6,97E+00	0,00E+00	3,85E+00	0,00E+00	0,00E+00

Indicator		Unit	B4	C1	C2	C3	C4	D
	CRU	kg	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	MFR	kg	0	0	0,00E+00	2,58E+00	0,00E+00	-5,03E-05
	MER	kg	0	0	0,00E+00	1,36E+01	0,00E+00	-6,07E-06
	EEE	MJ	0	0	0,00E+00	7,88E+00	0,00E+00	-3,82E-05
	EET	MJ	0	0	0,00E+00	1,19E+02	0,00E+00	-5,78E-04

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"
*INA Indicator Not Assessed

Biogenic Carbon Content

Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	4,72E-04
Biogenic carbon content in accompanying packaging	kg C	2,06E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, high voltage, hydro (kWh) - PL	ecoinvent 3.6	4,02	g CO2-eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Möbelfakta

Additional Environmental Information

Key Environmental Indicators

Key environmental indicators	Unit	A1-A3	A4	A1-C4	A1-D
GWPtotal	kg CO_2 -eq	50,14	1,65	80,26	77,25
Total energy consumption	MJ	846,62	25,97	1020,08	926,59
Amount of recycled materials	%	38,09			

Additional environmental impact indicators required in NPCR Part A for construction products						
Indicator	**Unit**	A1-A3	A4	A5	B2	B3
GWPIOBC	kg CO_2 -eq	5,72E+01	1,65E+00	8,00E-02	5,99E+00	2,69E-01

Indicator	Unit	B4	C1	C2	C3	C4	D
GWPIOBC	kg CO_2 -eq	0	0	2,57E-01	1,48E+01	7,38E-02	-4,14E+00

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Variants and Options

Key environmental indicators (A1-A3) for variants of this EPD				
Variants	**Weight (kg)**	**GWPtotal (kg CO_2 -eq)**	**Total energy consumption (MJ)**	**Amount of recycled materials (%)**
Profim Sorriso 10V (Xtreme/Camira) - No Packaging	13,56	53,02	720,35	18,24

Key environmental indicators (A1-A3) for options for this EPD				
Options	**Weight (kg)**	**GWPtotal (kg CO_2 -eq)**	**Total energy consumption (MJ)**	**Amount of recycled materials (%)**
Profim Sorriso 10V - Packaging (fully assembled)	4,55	-2,88	126,27	97,40

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21
Ruud et al., (2023) EPD generator for NPCR026 Part B for Furniture - Background information for EPD generator application and LCA data, LCA.no report number 01.23
NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.
NPCR 026 Part B for Furniture. Ver. 2.0 March 2022, EPD-Norge.

	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-norge.no
	Owner of the declaration: Flokk AS Drammensveien 145,, 0277 Oslo	Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com web: https://www.flokk.com
	Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6B,1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal